

WTBA Montreal (41')_16



Oil Pattern Distance 41 Reverse Brush Drop 34 Oil Per Board Multi ui Forward Oil Total 21.005 mL Reverse Oil Total 5.885 mL Volume Oil Total 26.89 mL Tank Configuration ALT Tank A Conditioner Kegel Tank B Conditioner Kegel Sime 5 53 16 4 16 3 21.22 25.30 mL Tank B Conditioner Kegel Sime 5 53 16 4 16 3 21.22 25.30 mL Tank B Conditioner Kegel Sime 1 69 16 3 3 19 127 152 25.30 mL Tank B Conditioner Kegel Sime 1 50 16 3 3 19 127 152 25.30 mL Tank B Conditioner Kegel Sime 1 50 16 3 3 19 127 122 25.30 mL Tank B Conditioner Kegel Sime 1 50 16 3 3 19 1224 28 3 25.30 mL Tank B Conditioner Kegel Sime 104 19 14 1 50 22 3 3 13 48 5.51 mL Tank B Conditioner Kegel S																				Your	LANES OUR	ASSION
Tank Configuration AIT Tank A Conditioner Kegel Tank B Conditioner Kegel Tank B Conditioner Kegel 124. 2R 5 53 18 4 100. 100.2 102.2 103.3 102.2 22.3 13.3 103.3 12.2 22.3 13.3 163.3 102.2 102.2 103.3 103.3 105.3 1.630 101.2 102.2 103.3 103.3 103.3 103.3 103.3 163.3 105.3 1.630 103.3 105.3 1.630	Oil Pattern D	istance		41	Rever	se Brus	h Droj	о С	34		Oi	I P	er B	oar	d						Mu	lti ul
START STOP LOADS MICS SPELD DUFFIG CROSED START TON 2 SL 2 R 5 53 18 4 185 0.0 10.2 9805 2 SL 5 R 1 50 18 3 11 12.2 2.5 1500 3 GL 68 1 50 18 3 12.2 2.5 1500 4 TL 7R 2 50 18 3 2.1 2.2 2.5 1500 6 100 108 3 21 2.2 2.5 12.0 1.0 3 21 2.20 2.2 1.0 2.3 7.2 2.5 1.0 0.0 2.3 1.3 3.3 3.6.3 3.1 6.0 0.0 0.0 1.0 0 50 2.2 3 13.2.3 3.6.3 3.1 6.0 0.0 5.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1	Forward Oil T	otal	21.005	5 mL	Rever	se Oil T	otal	5.88	5 mL		Vo	olu	me (Dil ⁻	Tota	al				2	26.89	9 mL
START STOP LOADS MICS SPILO DUMPER CROSSID START TON TON 1 2 L 2 R 5 33 18 4 185 00 10.2 10.2 9805 2 SL 5 R 1 so 18 3 29 12.7 12.5 15.0 4 TL 7 R 2 SO 18 3 24 12.25 25.3 15.0 6 101 1 SO 18 3 12.2 25.3 2.5 12.00 1 </td <td>Tank Configu</td> <td>iration</td> <td></td> <td>ALT</td> <td>Tank</td> <td>A Cond</td> <td>itione</td> <td>r I</td> <td>Kegel</td> <td></td> <td>Та</td> <td>nk</td> <td>вс</td> <td>onc</td> <td>litic</td> <td>ner</td> <td></td> <td></td> <td></td> <td></td> <td>К</td> <td>egel</td>	Tank Configu	iration		ALT	Tank	A Cond	itione	r I	Kegel		Та	nk	вс	onc	litic	ner					К	egel
1 2R 5 53 16 4 165 0.00 102 102 9805 2 SL 5R 1 50 16 3 210 27.152 25 1550 3 GL 6R 1 50 16 3 22 127.152 25 1550 5 GL 6R 1 50 16 3 122.28 25 1250 7 11. 7R 1 50 16 3 12.22 25 1500 7 11. 11R 1 50 16 3 17.27.8 30.33.4 3.1 750 10.14 14R 1 50 26 2 0 36.5 41.0 4.5 0 11.24. 2R 0 50 26 2 0 36.5 41.0 4.5 0 1 21.2 7 55 18 4 42 16.9 1.1 0.6 1.1 0.6 1.1 0.6 1.1 0.6 1.1 0.6 1.1 0.6 1.1	0																					<u> </u>
2 51 SR 1 50 16 3 31 102 12,7 2,5 1550 4 7L 7R 2 50 16 3 541 150 16 3 29 12,7 15,2 25 1550 5 8L 8R 1 50 16 3 24 22,3 12,5 12,5 15,5 10,5 11,1 11,1 11,1 11,1 150 16 3 21 22,8 2,5 12,5 16,5 11,2 12,1 2,7 10,1 2,5 2,50 10,1 1,1 1,50 16 3 17 27,4 2,5 9,50 1,1 1,1 1,1 1,7 2,5 2,5 1,1 <t< td=""><td></td><td>LOADS MICS</td><td>SPEED BU</td><td>FFER</td><td>CROSSED ST</td><td>ART END</td><td>FEET</td><td>T.OIL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>		LOADS MICS	SPEED BU	FFER	CROSSED ST	ART END	FEET	T.OIL														
i etc. etc. i so is 3 29 127 152 2.5 1450 i fill i fill i so i fill										Ш		Π	Ш	Ш	Ш	Ш	Ш	Ш	Ш	Ш		
4 TL 7R 2 50 18 3 54 152 20.3 5.1 2700 25 950 11 11 11 150 18 3 17 27.8 30.3 32.4 3.1 353 3.5 3.5 3.5 165 91 11 11 150 22 3 13 3.3 3.1 750 91 91 15 92 2.5 1.0 0 91 91 91 92 92 3.1 1.0 0 91	_									Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
6 108 1 50 18 3 21 22.8 2.5 1050 7 111. 118 1 50 18 3 19 22.3 2.5 1050 7 111. 118 1 50 18 3 19 22.3 2.5 1050 111. 118 1 50 22 3 15 30.3 3.4 3.1 750 111. 121. 28 0 50 26 2 0 36.5 31.0 4.5 0 112. 28 0 50 26 2 0 36.5 41.0 4.5 0 1 21.2 28 0 50 30 3 0 41.0 20.0 -21.0 0 1 101.8 8.2 255 18 4 42 16.9 -3.1 10.0 -2.1 0 -2.1 -2.1 -2.1 -2.1 -2.1 -2.1 -2.1 -2.1 -2.1 -2.1 -2.1 -	-									Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
7 111 11R 1 50 18 3 19 25.3 27.8 2.5 950 8 121 128 1 50 12 3 17 27.8 30.3 2.5 850 131 138 1 50 22 3 17 27.8 30.3 3.4 3.1 750 10 141 14R 1 50 22 3 13 33.4 3.5 3.1 650 1 22 28 0 50 20 3.65 3.1 650 1 <td>-</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>ĦĦ</td> <td></td> <td>Ħ</td> <td></td> <td>Ш</td> <td>Ш</td> <td>Ш</td> <td>Ш</td> <td></td> <td>Ħ</td> <td>ĦT</td> <td>Ш</td> <td>22</td>	-									ĦĦ		Ħ		Ш	Ш	Ш	Ш		Ħ	ĦT	Ш	22
i 121. 128. 1 50 16 3 17 27.8 30.3 2.5 850 9 131. 138. 1 50 22 3 15 30.3 33.4 3.1 750 10 14.1 150 22 3 15 30.3 33.4 3.1 750 11 24. 28 0 50 26 2 0 36.5 41.0 4.5 0 57MT 500 30 3 0 41.0 20.0 21.0 0 0 1.0 0 1.0 0 1.0 1.0 0 1.0 0 1.0 0 1.0 0 1.0 0 0 1.0 0 0 1.0 0 0 1.0 0 <td>-</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Ш</td> <td></td> <td></td> <td>Ш</td> <td>Ш</td> <td>Ш</td> <td>Ш</td> <td>Ш</td> <td></td> <td>Ш</td> <td>Ш</td> <td></td> <td></td>	-									Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
9 131 13R 1 50 22 3 15 30.3 33.4 3.1 750 10 14L 14R 1 50 22 3 13 33.4 36.5 3.1 650 11 2L 2R 0 50 26 2 0 36.5 3.1 650 12L 2R 0 50 30 3 0 41.0 200 -21.0 0 2 12L 10R 1 55 22 3 19 200 15.9 -3.1 1045 3 11L 9R 2 55 18 4 46 11.8 57.1 12.310 4 10L 8R 2 55 18 4 46 11.8 57.1 12.310 5 2L 2R 0 50 18 4 6.7 0.0 -6.7 0 Cleaner Ratio Main Mix 4:1 4:1 -1 -1 -1 -1 -1 -1 -1										Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
11 2L 2R 0 50 26 2 0 36.5 41.0 4.5 0 5TART STOP LOADS MICS SPEED BUFFER CROSSED START END FET TOL 1 2L 2R 0 50 30 3 0 41.0 20.0 -21.0 0 2 12L 10R 1 55 22 3 19 20.0 16.9 -3.1 1045 3 11L 9R 2 55 18 4 42 16.8 -5.1 2310 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 -4:1 <										ĦĦ		Ħ	Ħ	Ħ	Ш	ĦĦ	Ш	Ⅲ	ĦĦ	ĦĦ	Ш	5
START STOP LOADS MICS SPEED EUFFER CROSED START END FEET TOL 1 21 28 0 50 30 3 0 41.0 20.0 21.0 10 3 11L 98 2 55 18 4 42 16.9 1.3 1045 3 11L 98 2 55 18 4 42 16.9 1.8 5.7 20.0 6.7 0.0 -6.7 0	10 14L 14R	1 50	22	3	13 3	3.4 36.5	3.1	650		Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
START STOP LOADS MICS SPEED BUFFER CROSSED START NO FET YOK 1 2 2 0 50 30 3 0 41.0 20.0 -21.0 0 0 1 2 1 19 2.00 16.9 -3.1 104.5 210 0 5 22 3 19 20.0 16.9 -3.1 104.5 210 4 101.8 87.7 2310 230 -5.1 230 5 21 28 0 50 18 4 46 11.8 6.7 0.0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7 0 -6.7	11 2L 2R	0 50	26	2	0 3	6.5 41.0	4.5	0		Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
START STOP LOADS MICS SPEED BUFFER CROSSED START END FET TOIL 1 24 2R 0 50 30 3 0 410 20.0 -21.0 0 2 12L 10R 1 55 22 3 19 20.0 16.9 -3.1 1045 3 11L 9R 2 55 18 4 42 15.1 2230 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main <mix< td=""> 4:1 -</mix<>										ĦĦ		Ħ	₩	Ħ	Ⅲ	₩	Ш	₩	₩	ĦĦ		- 52
START STOP LOADS MICS SPEED BUFFER CROSSED START END FET TOIL 1 24 2R 0 50 30 3 0 410 20.0 -21.0 0 2 12L 10R 1 55 22 3 19 20.0 16.9 -3.1 1045 3 11L 9R 2 55 18 4 42 15.1 2230 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main <mix< td=""> 4:1 -</mix<>										Ш			Ш	Ш	Ш	Ш	Ш		Ш	Ш		
START STOP LOADS MICS SPEED BUFFER CROSSED START END FET TOIL 1 24 2R 0 50 30 3 0 410 20.0 -21.0 0 2 12L 10R 1 55 22 3 19 20.0 16.9 -3.1 1045 3 11L 9R 2 55 18 4 42 15.1 2230 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main <mix< td=""> 4:1 -</mix<>										Ш				111								
1 2L 2R 0 50 30 3 0 41.0 20.0 -21.0 0 2 12L 10R 1 55 22 3 19 20.0 16.9 -3.1 1045 3 11L 9R 2 55 18 4 42 16.9 1.8 5.1 2510 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1										Ħ		Ħ		Ħ			Ш		Ħ	ĦĦ		육
2 12L 10R 1 55 22 3 19 20.0 16.9 -3.1 1045 3 11L 9R 2 55 18 4 42 16.9 11.8 -5.1 2310 4 10L 8R 2 55 18 4 46 11.8 -5.1 2310 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 -			SPEED BU	FFER	CROSSED ST/	ART END	FEET	T.OIL		Ш				Ш			Ш		Ш	Ш		
3 11L 9R 2 55 18 4 42 16.9 11.8 -5.1 2310 4 10L 8R 2 55 18 4 46 11.8 6.7 -5.1 2330 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 -										Ш									111	Ш		
4 10L 8R 2 55 18 4 46 11.8 6.7 -5.1 2530 5 2L 2R 0 50 18 4 0 6.7 0.0 -6.7 0 Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 -										₩		Ħ		₩	₩	₩	H		₩	₩	HH	- 82
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R	-									Ш				Ш	Ш	ш	Ш	HI	Ш	Ш	Ш	
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R	5 2L 2R	0 50	18	4	0	6.7 0.0	-6.7	0						Ш	Ш	ш	Ш		Ш	Ш		
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R										₩		Ħ		₩	₩	₩	H		₩	₩	HH	8
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R										Ш			Ш	Ш	Ш	ш	Ш		Ш	Ш	1111	
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R										Ш				Ш	Ш	ш	Ш		Ш	Ш		
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R										₩		Ħ	₩	₩	₩	₩	H	₩	₩	₩	HH	2
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R										Ш			Ш	Ш	Ш	ш	Ш		Ш	Ш	1111	
Cleaner Ratio Main Mix 4:1 Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R										Ш		П	Ш	Ш	Ш	ш	Ш		Ш	Ш	ш	
Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:17R-13R 18L-18R:12R-8R										₩		Ħ								Ht		-≈
Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:17R-13R 18L-18R:12R-8R										Ш										Ш	Ш	
Cleaner Ratio Back End Mix 4:1 Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:17R-13R 18L-18R:12R-8R										Ш										ш	ш	
Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R	Cleaner Ratio	Main Mix			4:1					₩		Ħ								H	HH	-1℃
Cleaner Ratio Back End Distance 59 Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R	Cleaner Ratio	Back End	Mix		4:1					Ш									ш		Ш	
Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50 Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R				· 🗅						Ш	ПΗ								Ш	11	Ш	
Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R						50				m	₩											2
	Duiter Krivi. 4	= 120 3	= 500	Z = 2	200 1 = 0	50				Ш												
										Ш												
																						~
																						7
	Item	3L-7L:18L	-18R	8L	-12L:18L-18R	13	-17L:18L-	18R	18L-1	BR:17	R-13R		18	-18R	:12R-8	BR		18	L-18R:	7R-3F	2	
Description Outside Track:Middle Middle Track:Middle Inside Track:Middle Middle: Inside Track Middle:Middle Track Middle:Outside Track	Description	Outside Trac	k:Middle	Middle	e Track:Midd	lle Inside	Track:Mi	ddle	Middle:	Inside	e Track	. N	liddle	e:Mid	Idle 1	Frack	Mi	ddle:	Dutsic	le Tr	ack	

escription	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	Mlddle: Inside Track	Middle:Middle Track	Middle:Outside Track		
rack Zone Ratio 3.1		1.49	1.01	1.01	1.29	3.1		
1500 1350 1200 900 750 600 450 300 150 0 								